

IOT-S500LGT

Light Sensor Data Sheet

LINOVISION



IOT-S500LGT is designed for measuring light in harsh environments and transmitting data using LoRaWAN® technology. With this low power consumption technology, IOT-S500LGT can work up to 10 years with 19000 mAh battery. Combining with Linovision LoRaWAN® gateway and Linovision IoT Cloud solution, users can manage all sensor data remotely and visually.

IOT-S500LGT is widely used for outdoor applications like smart agriculture, urban lighting, etc.

◆ Features

- Wide measuring range and high precision
- Ultra-wide-distance transmission up to line of sight of 10km
- IP66 waterproof enclosure for harsh environment applications
- Built-in 19000 mAh replaceable battery and work for 10 years without replacement
- Equipped with NFC for easy configuration
- Compliant with standard LoRaWAN® gateways and network servers
- Quick and easy management with Linovision IoT Cloud solution

◆ Applications

- Smart buildings
- Urban lighting
- Greenhouse control
- Smart agriculture
- Weather monitoring

◆ Specifications

Wireless Transmission	
Technology	LoRaWAN®
Frequency	CN470/IN865/RU864/EU868/US915/AU915/KR920/AS923
Tx Power	16dBm(868)/20dBm(915)/19dBm(470)
Sensitivity	-147dBm @300bps
Mode	OTAA/ABP Class A
Measurement	
Range	0 - 100000 lux
Accuracy	±3%
Resolution	1 lux
Operation	
Power On & Off	NFC, power button (Internal)
Configuration	Mobile APP(via NFC) or PC software(via USB Type-C)
Physical Characteristics	
Cable Length	3 m
Power Supply	19000 mAh Li-SOCL ₂ battery (ER34615)
Battery Life*	4 years (10 min interval, SF12) >10 years (10 min interval, SF7)
Operating Temperature	-30°C to +60°C
Relative Humidity	0% to 100% (non-condensing)
Ingress Protection	IP66(Transceiver)/IP65(Light Sensor)
Dimension	Transceiver: 105.4 × 71 × 69.5 mm (4.1 × 2.8 × 2.7 in) Light Sensor: 64 × 58 × 34 mm (2.5 × 2.3 × 1.3 in)
Installation	Pole, wall or DIN Rail Mounting

* Tested under laboratory conditions and for guideline purposes only.