

4MP LPR Bullet Network Camera

IPC LPR NDAA(4MP)



Key Features



- High quality image with 4MP, 1/1.8"CMOS sensor
- 4MP (2688*1520) @ 30fps
- H.265, H.264
- 120dB true WDR technology enables clear image in strong light scene
- 4 warm light LEDs, up to 164FT IR range
- Audio Line In/Out, Alarm Line In/Out
- IP67, IK10 Rated

Specifications

Camera	IPC LPR NDAA(4MP)
Sensor	1/1.8" CMOS
Lens	8 ~ 32mm @ f1.7, AF automatic focusing and motorized zoom lens
Angle of view (H)	42.4°~ 15.9°
Angle of View (V)	23.9°~ 9.8°
Angle of View (D)	52.5°~17.8°
Shutter	Auto/Manual, shutter time: 1/30 ~ 1/100000s
Minimum Illumination	0.002 Lux (F1.7, AGC ON)
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>56 dB
IR Range	Up to 164FT
IR On/Off Control	Auto/Manual
WDR	120dB
Video	
Video Compression	H.265, H.264
Frame Rate	Main Stream: 4MP (2688*1520), Max 30fps Sub Stream: 720P (1920*1080), Max 30fps
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 areas
ROI	Support
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital Noise Reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°/90°Clockwise/90° Counter-clockwise
HLC	Support
BLC	Support
Defog	Digital Defog
Intelligent	
Application Scenario	≤ 50 mph for regular roads
Vehicle Detection Mode	Supports video detection
License Plate Number Recognition	Supports recognition of license plates with numbers and letters
List Configuration	Supports allowlist and blocklist
Events	
Basic Detection	Motion detection, tampering alarm, audio detection
General Function	Watermark, IP address filtering, alarm input, alarm output, access policy, ARP protection, RTSP authentication, user authentication
Storage	
Edge Storage	Supports ANR with Micro SD, up to 256GB
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), SDK
Interface	
Network Interface	1 x 10/100M RJ45

Alarm I/O	2 x input (up to DC5V); 1 x output (AC125V/0.3A), DC30V/1A
Audio	1 input, 1 output
Storage	1 microSD card slot
Certifications	
Certifications	CE-EMC (EN 55032:2015+A11:2020+A1:2020, EN 61000-3-3:2013+A1:2019+A2:2021, EN IEC 61000-3-2:2019+A1:2021, EN 50130-4:2011+A1:2014) FCC(FCC CFR 47 part15 B, ANSI C63.4 2014)
General	
Power	DC12V±25%, PoE (IEEE 802.3at)
	Power consumption: Max 20W
Dimensions (L × W × H)	16.0" × 5.0" × 5.1"
Net Weight	5 lb
Material	Metal
Working Environment	-40°C ~ 60°C (-40°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-40°C ~ 70°C (-40°F ~ 158°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Ingress Protection	IP67, IK10
Reset Button	Support