

## MUW04H-1S90

Modular Network Underwater Camera KIT



This is a modular Underwater Camera KIT, featuring 1080P true HD resolution. This kit includes a DVR and a modular underwater camera by default. The camera (product SKU: MUWS90) is equipped with 12pcs brightness adjustable white LED and a 33ft (10 meters) waterproof cable, can be used up to 33ft (10 meters) underwater. The DVR (product SKU: XVR04H) supports Local HDMI TV monitor output. It offers intuitive web GUI (compatible to Chrome/Safari/IE/Edge and no plug-in or ActiveX is required) and free mobile App with Cloud access. It supports API for third-party integration. The DVR has 4 BNC ports, allowing up to 4 cameras to be connected as a kit.

### Features

- 304 stainless steel and professional IP68 waterproof housing
- 1080P SONY CMOS sensor
- Wide view angle
- Brightness adjustable LEDs
- H.265 Pro+/H.265 Pro/H.265/H.264 video compression
- HDMI/VGA output
- Remote access via Intuitive WEB GUI
- Free mobile app with cloud access
- Offer API for 3rd party access
- Easy expanding (can add up to 4 cameras)


## Specification

| Mode             | MUW04H-1S90          |                                                                                     |
|------------------|----------------------|-------------------------------------------------------------------------------------|
| Camera           | Image Sensor         | 2MP high-performance Sony CMOS                                                      |
|                  | Lens Type            | 2.8mm fixed lens , FOV 90°                                                          |
|                  | TV Coding System     | PAL(EU)/NTSC(US)                                                                    |
|                  | Effective Pixels     | 1920(H)×1080(V)                                                                     |
|                  | Electronic Shutter   | AUTO                                                                                |
|                  | Light Source         | 12pcs Brightness Adjustable White LED                                               |
|                  | WDR                  | Digital WDR                                                                         |
|                  | White Balance        | Auto                                                                                |
|                  | Waterproof Rate      | IP68                                                                                |
|                  | Operating Conditions | -4°F to 140°F (-20 °C - 60 °C)                                                      |
|                  | Power Supply         | DC12V 1A                                                                            |
|                  | Power Consumption    | ≤ 1W                                                                                |
|                  | Length of Cable      | 33 feet (10 meters) waterproof cable                                                |
|                  | Dimension            | 1.16" x 2.63"(29.5mm x 67mm)                                                        |
|                  | Weight               | 0.88lb (400g) with waterproof cable                                                 |
| Housing Material | 304 stainless steel  |                                                                                     |
| DVR              | Video Coding         | H.265+/H.265/H.264+/H.264                                                           |
|                  | Video Input          | Up to 4 cameras inputs                                                              |
|                  | HD Video Input       | HD-TVI                                                                              |
|                  | Video Output         | 1 × VGA/HDMI (1920 x 1080/60Hz, 1280 x 1024/60Hz, 1280 x 720/60Hz, 1024 x 768/60Hz) |
|                  | Encoding resolution  | 4 MP/3 MP/1080p/720p/VGA/WD1/4CIF/CIF                                               |
|                  | Incoming Bandwidth   | 24 Mbps                                                                             |
|                  | Audio                | 1-ch Audio input , 1-ch Audio output (RCA Interface)                                |
|                  | Playback             | 4-ch Synchronous Playback                                                           |
|                  | Storage Capacity     | 1 SATA interface, up to 6 TB capacity                                               |
|                  | Remote Access        | WEB, Mobile App (Guarding Vision)                                                   |
|                  | Operating Conditions | +14 °F to +131 °F (-10 °C to +55 °C)                                                |
|                  | Dimension(L×W×H)     | 7.90" x 7.90" x 1.80" (200mm x 200mm x 45mm)                                        |
|                  | Weight               | 1.02lb (463g)                                                                       |
|                  | Power Supply         | 12V 1.5A                                                                            |
|                  | Power Consumption    | ≤ 8W                                                                                |

Camera's interface




DVR backward interface




Dimension

Camera's Dimension



DVR's Dimension



## Package Included



x 1

DVR



x 1

MUWS90 with 33ft Cable



x 1

Mouse



x 1

Hard Drive Data Cable



x 1

Camera Power Adapter



x 1

DVR Power Adapter



x 1

User Manual