

POE-Switch1108GP

Gigabit 11 Ports Outdoor PoE Switch with 8 PoE Ports and Passive 24V PoE for Ubiquiti Wireless Bridge



Outstanding Features

- IP65 Waterproof Enclosure and 6kV Surge Protection
- 8x IEEE802.3af/at/bt PoE ports, 2 of them are Gigabit 60W POE++ ports
- 2x GE and 1x SFP uplinks
- Large-area pure aluminum heat sink and front air vents prevent the internal chipset from overheating
- Support 24V passive PoE output for Nanostation bridge or wireless AP, it can also output DC12V or DC 24V
- Support PoE watchdog, auto-detect the freezing POE device, and then auto-reboot the specific POE port
- Support pole mount and wall mount (brackets included)

Specification

Hardware Features	
Hardware Version	V2
Interface	6 10/100Mbps RJ45 PoE Ports 2 100/1000Mbps RJ45 PoE Ports 2 100/1000Mbps Uplink Ports 1 100/1000Mbps SFP Slot
PoE Ports	Port 1-6: 802.3af/at Port 7- 8: 802.3 bt 60W
Network Media	10Base-T: Pair 2 Category 3(cat 3) and above UTP/STP(≤100m) 100Base-TX: Pair 2 Category 5(cat 5) and above UTP/STP(≤100m) 1000BASE-TX: 6 Category and above UTP(≤150m)
Power Supply	AC 110~240V 50/60HZ
Power Budget	120W
Exchange Capacity	11.2Gbps
Packet Forwarding Rate	8.33Mpps
Mac Address Table	4k
Protection	6kV PoE Surge Protection 10kV AC Surge Protection
Jumbo Frame	10240Bytes
SOFTWARE FEATURES	
Advanced Functions	Mac Address Auto-Learning And Auto-Aging Store and forward IEEE 802.3x flow control for Full-duplex Mode Backpressure for Half-duplex Mode
OTHERS	
Certification	CE, FCC, RoHS
Package Dimension	340×315×120 mm
Switch Dimension	350×255×90 mm
Gross Weight	1.95kg
Net Weight	1.4kg
Package Contents	1 × PoE Switch 1 × Power cord 1 × Quick Installation Guide 1 × Wall mounting KIT 1 × Pole mounting KIT 6 × Screws

Specification

Environment	Working Temperature: -30°C ~70°C(22°F~158 °F)
	Storage Temperature: -40°C~70 °C (-40~158 °F)
	Operating Humidity: 10~90% RH non-condensing
	Storage Humidity: 5~90% RH non-condensing