

OUTDOOR LTE/WI-FI /GPS/BLUETOOTH ANTENNA FOR RUTX11 AND RUTM11 ROUTERS

IP67

Water and dust-resistant for ultimate outdoor reliability

OMNIDIRECTIONAL

Designed for reliable signal coverage from every direction

INTEGRATED MOUNTING BRACKET

Quick and easy pole/mast mounting

PERFECT ROUTER MATCH

Compatible and designed to contain select Teltonika routers

The antenna is supplied without a router







TECHNICAL DATA

LTE ANTENNA

| Frequency Range | 617 ~ 960, 1700 ~ 2700, 3300 ~ 4300 MHz |
|--------------------------|---|
| Polarisation | Vertical |
| Radiation pattern type | Omnidirectional |
| Gain | Max 4.5 dBi |
| V.S.W.R | <2.50 |
| Impedance | 50 Ω |
| Connector type and count | 2x SMA male |

BT ANTENNA

| Frequency Range | 2200 ~ 2700 MHz |
|--------------------------|-----------------|
| Polarisation | Vertical |
| Gain | 2 dBi |
| V.S.W.R | <2.00 |
| Impedance | 50 Ω |
| Connector type and count | 1x RP-SMA male |
| | |

The Bluetooth antenna is not utilised when used with the RUTM11

WI-FI ANTENNA

| Frequency Range | 2400 ~ 2500, 4700 ~ 6000 MHz |
|--------------------------|------------------------------|
| Polarisation | Vertical |
| Radiation pattern type | Omnidirectional |
| Gain | Max 7.5 dBi |
| V.S.W.R | <2.00 |
| Impedance | 50 Ω |
| Connector type and count | 2x RP-SMA male |

GNSS ANTENNA

| Frequency Range | 1560 ~ 1610 MHz |
|--------------------------|-----------------|
| Polarisation | RHCP |
| Gain | 28 dBi |
| V.S.W.R | <2.00 |
| Impedance | 50 Ω |
| Connector type and count | 1x SMA male |
| Current consumption | 2.5 - 6.5 mA |
| Supply voltage | 2.5 - 6.5 VDC |

MECHANICAL/ENVIRONMENTAL

| Cable | 5x RG316, 1x RG174 |
|-----------------------|---------------------|
| Operating Temperature | -40 °C to 75 °C |
| Mounting Method | Wall, ceiling, mast |
| IP rating | IP67 |
| Weight | 1500 g |
| RoHS compliant | |



